MSDS 说明书



www.xiyashiji.com

化学品安全技术说明书

填表时间 2020-03-09

打印时间 2025-07-04

MSDS标题 HB FULLER HARDENER 2 MSDS报告 产品标题 2,4-二异氰酸甲苯酯;2,4-二异酸甲苯酯 CAS号 584-84-9 化学品及企业标识 **PRODUCT NAME HB FULLER HARDENER 2 NFPA** Flammability 3 2 Toxicity **Body Contact** 2 Reactivity 0 Chronic 2 SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

Hardener for two part PVC adhesive primer. Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers. CONTAINS free organic isocyanate. Mixing and application requires special precautions and use of personal protective gear [APMF]. CAUTION: isocyanates are strong respiratory sensitizers and skin sensitizers. Sensitized people can react to very low levels of airborne isocyanates and should not be required to work with these materials.

SYNONYMS

"polyisocyanate isocyanate hardener resin solution Intraflo misspelling"

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

Harmful by inhalation. Irritating to eyes. May cause SENSITIZATION by skin contact. HARMFUL - May cause lung damage if swallowed. Highly flammable. Repeated exposure may cause skin dryness and cracking. Vapors may cause dizziness or suffocation.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre- existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

This material can cause eye irritation and damage in some persons. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Sensitization may result in allergic dermatitis responses includingrash, itching, hives or swelling of extremities. Toxic effects may result from skin absorption. Bare unprotected skin should not be exposed to this material.

INHALED

The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. The vapor/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary edema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia. Gastrointestinal disturbances are characterized by nausea and vomiting. Pulmonary sensitization may produce asthmatic reactions ranging from minor breathing difficulties to severe allergic attacks; this may occur following a single acute exposure or may develop without warning for several hours after exposure. Sensitized people can react to very low doses, and should not be allowed to work in situations allowing exposure to this material. Continued exposure of sensitized persons may lead to possible long term respiratory impairment. Inhalation hazard is increased at higher temperatures. Reactions may not occur on exposure but response may be delayed with symptoms only appearing many hours later. Inhalation of vapor may aggravate a pre-existing respiratory condition such as asthma, bronchitis, emphysema.

CHRONIC HEALTH EFFECTS

Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population.

Principal routes of exposure are usually by inhalation of vapor and skin contact with the material. Sensitization may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitized persons should not be allowed to work in situations where exposure may occur. Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapor, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.