MSDS 说明书



www.xiyashiji.com

化学品安全技术说明书

填表时间 2019-12-31

打印时间 2025-09-04

MSDS标题

KINETIK COMBINED ACID BUFFER REAGENT MSDS报告

产品标题

甲醇;木精

CAS号

67-56-1

化学品及企业标识

PRODUCT NAME

KINETIK COMBINED ACID BUFFER REAGENT

NFPA

Flammability	0
Toxicity	2
Body Contact	1
Reactivity	0
Chronic	2
SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4	

PRODUCT USE

Laboratory reagent for use with Coulimetric Chloride Meter.

SYNONYMS

"laboratory reagent for use with coulimetric chloride meter", Kinetick, Kinetic

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre- existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Considered an unlikely route of entry in commercial/industrial environments. Ingestion may result in nausea, abdominal irritation, pain and vomiting.

EYE

Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn). The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapors especially at higher temperatures. Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision. Continued or severe exposures may cause damage to optic nerves, which may become severe with permanent visual impairment even blindness resulting. WARNING: Methanol is only slowly eliminated from the body and should be regarded as a cumulative poison which cannot be made non-harmful [CCINFO]. Long-term exposure to methanol vapor, at concentrations exceeding 3000 ppm, may produce cumulative effects characterized by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result. Some individuals show severe eye damage following prolonged exposure to 800 ppm of the vapor.