

www.xiyashiji.com

### 化学品安全技术说明书

填表时间 2019-12-30

打印时间 2025-04-05

### MSDS标题

KIMBERLY CLARK MILLICENT MILL WASTE GLUE MSDS报告

## 产品标题

聚乙二醇;聚乙二醇200;聚乙二醇300;聚乙二醇400;聚乙二醇600

#### CAS号

25322-68-3

化学品及企业标识

# **PRODUCT NAME**

KIMBERLY CLARK MILLICENT MILL WASTE GLUE

# **NFPA**

Flammability	0
Toxicity	0
Body Contact	1
Reactivity	0
Chronic	2

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

# **PRODUCT USE**

Waste glue.

#### **SYNONYMS**

"waste adhesive"

### CANADIAN WHMIS SYMBOLS

#### **EMERGENCY OVERVIEW**

**RISK** 

#### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

#### **SWALLOWED**

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Considered an unlikely route of entry in commercial/industrial environments. Ingestion may result in nausea, abdominal irritation, pain and diarrhea.

#### **FYF**

Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

#### **SKIN**

The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

#### **INHALED**

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product.

# **CHRONIC HEALTH EFFECTS**

Primary route of exposure is usually by skin contact. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapor, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

