

化 学 品 安 全 技 术 说 明 书

填表时间 2019-12-30

打印时间 2025-12-05

MSDS标题

WITCO VIBRACURE A-510 MSDS报告

产品标题

丁隔二醇;1,4-二羟丁烷;1,4-二羟基丁烷;丁撑二醇

CAS号

110-63-4

化学品及企业标识

PRODUCT NAME

WITCO VIBRACURE A-510

NFPA

Flammability	1
Toxicity	2
Body Contact	2
Reactivity	1
Chronic	0
SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4	

PRODUCT USE

Polyol- based curative for urethane products.

SYNONYMS

polyol, curative, urethane

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

Harmful if swallowed.

HARMFUL - May cause lung damage if swallowed.

Vapors may cause dizziness or suffocation.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma. Digestive symptoms may include nausea, vomiting and diarrhea. Aspiration is much more dangerous than ingestion because lung damage can occur and the substance is absorbed into the body. Alcohols with ring structures and secondary and tertiary alcohols cause more severe symptoms, as do heavier alcohols.

EYE

Although the liquid is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation may produce health damage*. There is some evidence to suggest that this material, if inhaled, can irritate the throat and lungs of some persons. Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioral changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. Nausea and vomiting are seen, and liver and kidney damage is possible as well following massive exposures. Symptoms are more acute the more carbons there are in the alcohol. The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified using animal models). Nevertheless, adverse effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Acute effects from inhalation of high concentrations of vapor may be nose, throat and chest irritation with coughing, sneezing and possible nausea.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified using animal models); nevertheless exposure by all routes should be minimized as a matter of course.