

化 学 品 安 全 技 术 说 明 书

填表时间 2019-12-31

打印时间 2026-04-19

MSDS标题

WATTYL DIMET 130 WOOD STOP TIMBER PUTTY MSDS报告

产品标题

纳米硫酸钡超细硫酸钡

CAS号

7727-43-7

化学品及企业标识

PRODUCT NAME

WATTYL DIMET 130 WOOD STOP TIMBER PUTTY

NFPA

Flammability	3
Toxicity	2
Body Contact	2
Reactivity	1
Chronic	3

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

Applied using a hand trowel or spreader. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. A quick drying solvent- based filler putty used to repair minor imperfections on timber surfaces.

SYNONYMS

"130 line Timber putty timber repair putty"

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

May impair fertility.

May cause harm to the unborn child.

Harmful by inhalation, in contact with skin and if swallowed.

Highly flammable.

Vapors may cause dizziness or suffocation.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

There is some evidence to suggest that this material can cause eye irritation and damage in some persons. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.

SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. The liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis. Toxic effects may result from skin absorption. Exposure limits

with "skin" notation indicate that vapor and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapor inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard. The material may accentuate any pre-existing dermatitis condition.

INHALED

The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation hazard is increased at higher temperatures. Inhalation of high concentrations of gas/vapor causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material. Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

Principal routes of exposure are usually by skin contact with liquid and inhalation of vapor/spray mist. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]. Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.