

www.xiyashiji.com

## 化学品安全技术说明书

填表时间 2019-12-30

打印时间 2025-11-05

## MSDS标题

WOODCHEM T0102 MSDS报告

#### 产品标题

尿素甲醛树脂;脲甲醛树脂

## CAS号

9011-05-6

化学品及企业标识

# **PRODUCT NAME**

WOODCHEM T0102

## **NFPA**

Flammability	0
Toxicity	0
Body Contact	2
Reactivity	0
Chronic	2

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

# **PRODUCT USE**

Used in composite board. Cured by heating.

#### CANADIAN WHMIS SYMBOLS

## **EMERGENCY OVERVIEW**

#### **RISK**

May cause SENSITIZATION by skin contact. Limited evidence of a carcinogenic effect. Irritating to eyes and skin.

## POTENTIAL HEALTH EFFECTS

#### **ACUTE HEALTH EFFECTS**

#### **SWALLOWED**

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Ingestion may result in nausea, abdominal irritation, pain and vomiting. Considered an unlikely route of entry in commercial/industrial environments.

#### **EYE**

This material can cause eye irritation and damage in some persons. The vapor is.

#### SKIN

This material can cause inflammation of the skin oncontact in some persons. Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions. Sensitization may result in allergic dermatitis responses includingrash, itching, hives or swelling of extremities.

#### **INHALED**

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation hazard is increased at higher temperatures.

## **CHRONIC HEALTH EFFECTS**

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population.

Principal routes of exposure are usually by skin contact/eye contact and inhalation of vapor. The material contains residues of free formaldehyde which may irritate the eyes or mucous membranes and produce an allergic response if used in confined spaces or heated.

