

化学品安全技术说明书

填表时间 2020-02-10

打印时间 2025-04-07

MSDS标题

VERTEX SOFT NF LIQUID MSDS报告

产品标题

有机玻璃单体;异丁烯酸甲酯

CAS号

80-62-6

化学品及企业标识

PRODUCT NAME

VERTEX SOFT NF LIQUID

NFPA

Flammability	3
Toxicity	2
Body Contact	2
Reactivity	2
Chronic	2

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

Used according to manufacturer' s directions.

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

May cause SENSITIZATION by skin contact.
Irritating to eyes, respiratory system and skin.
Highly flammable.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, unintentional ingestion is not thought to be cause for concern.

EYE

This material can cause eye irritation and damage in some persons.

SKIN

This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition. Skin contact is not thought to have harmful health effects, however the material may still produce health damage following entry through wounds, lesions or abrasions. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. If exposure to highly concentrated vapor atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma

and unless resuscitated - death. There is some evidence to suggest that this material can cause, if inhaled once, irreversible damage of organs.

CHRONIC HEALTH EFFECTS

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. There is some evidence that inhaling this product is more likely to cause a sensitization reaction in some persons compared to the general population. Skin contact with the material is more likely to cause a sensitization reaction in some persons compared to the general population. There is some evidence to suggest that this material can cause, if inhaled once, irreversible damage of organs. Sensitization may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitized persons should not be allowed to work in situations where exposure may occur.