

化学品安全技术说明书

填表时间 2019-12-30

打印时间 2026-02-23

MSDS标题

N-NONANE MSDS报告

产品标题

壬烷

CAS号

111-84-2

化学品及企业标识

PRODUCT NAME

N-NONANE

NFPA

Flammability	2
Toxicity	2
Body Contact	2
Reactivity	1
Chronic	0

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

Organic syntheses; biodegradable detergents; distillation chaser.

SYNONYMS

C9-H20, CH3(CH2)7CH3, normal-nonane

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

HARMFUL - May cause lung damage if swallowed.
Flammable.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed. Ingestion may result in nausea, pain and vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn). The vapour and liquid both produce eye discomfort. Tearing and reddening of the eyes are symptomatic of overexposure. Higher levels of vapour are generated with increased temperature and engineering controls should be introduced when any discomfort is experienced following exposure to mists or vapour.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. The

liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis. The material may accentuate any pre-existing skin condition. Open cuts, abraded or irritated skin should not be exposed to this material.

INHALED

Inhalation may produce health damage*. The material is not thought to produce respiratory irritation (as classified using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapor may aggravate a pre-existing respiratory condition. Inhalation of high concentrations of gas/vapor causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapors especially at higher temperatures. No human exposure data available. For this reason health effects described are based on experience with chemically related materials. As with any chemical product, contact with unprotected bare skin; inhalation of vapor, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.