

化 学 品 安 全 技 术 说 明 书

填表时间 2019-12-30

打印时间 2026-01-07

MSDS标题

ZHEJIANG MONOISOPROPYLAMINE 70% SOLUTION MSDS 报告

产品标题

2-丙胺; 甲基乙胺; 异丙基胺; 一异丙胺; 2-氨基丙烷

CAS号

75-31-0

化学品及企业标识

PRODUCT NAME

ZHEJIANG MONOISOPROPYLAMINE 70% SOLUTION

NFPA

Flammability	3
Toxicity	3
Body Contact	3
Reactivity	0
Chronic	2

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Chemical intermediate.

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

Harmful by inhalation.

Causes burns.

Risk of serious damage to eyes.

Toxic in contact with skin and if swallowed.

Highly flammable.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Amines without benzene rings when swallowed are absorbed throughout the gut. Corrosive action may cause damage throughout the gastrointestinal tract. They are removed through the liver, kidney and intestinal mucosa by enzyme breakdown.

EYE

If applied to the eyes, this material causes severe eye damage. The material can produce chemical burns to the eye following direct contact. Vapors or mists may be extremely irritating. Vapors of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in "halos" around lights. This effect is temporary, lasting only for a few hours. However this condition can reduce the efficiency of undertaking skilled tasks, such as driving a car. Direct eye contact with liquid volatile amines may produce eye damage, permanent for the lighter species. This material can cause eye irritation and damage in some persons.

SKIN

Skin contact with the material may produce toxic effects; systemic effects may result following absorption. The material can produce chemical burns following direct contact with the skin. Volatile amine vapors produce irritation and inflammation of the skin. Direct contact can cause burns. They

may be absorbed through the skin and cause similar effects to swallowing, leading to death. The skin may exhibit whiteness, redness and wheals. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

If inhaled, this material can irritate the throat and lungs of some persons. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. Vapor is heavier than air and may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary edema. Inhalation of amine vapors may cause irritation of the mucous membrane of the nose and throat, and lung irritation with respiratory distress and cough. Swelling and inflammation of the respiratory tract is seen in serious cases; with headache, nausea, faintness and anxiety. There may also be wheezing. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

CHRONIC HEALTH EFFECTS

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis. Limited evidence suggests that repeated or long-term occupational exposure

may produce cumulative health effects involving organs or biochemical systems.

xiya