

化 学 品 安 全 技 术 说 明 书

填表时间 2019-12-31

打印时间 2026-03-14

MSDS标题

JAL F186 TRUCK VEHICLE WASHING DETERGENT MSDS报告

产品标题

3-甲氧基-3-甲基-1-丁醇;3-甲基-3-甲氧基丁醇

CAS号

56539-66-3

化学品及企业标识

PRODUCT NAME

JAL F186 TRUCK VEHICLE WASHING DETERGENT

NFPA

Flammability	0
Toxicity	1
Body Contact	1
Reactivity	0
Chronic	2

SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

PRODUCT USE

Vehicle degreaser/cleaner usually applied by spraying and wiping off.

SYNONYMS

"industrial cleaner", "heavy duty detergent", "commercial cleaning liquid", "truck washing liquid"

CANADIAN WHMIS SYMBOLS

EMERGENCY OVERVIEW

RISK

HARMFUL - May cause lung damage if swallowed.

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects, the material may still be damaging to the health of the individual following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality (death) rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern. Ingestion may result in nausea, abdominal irritation, pain and vomiting. Considered an unlikely route of entry in commercial/industrial environments.

EYE

Although the material is not thought to be an irritant, direct contact with the eye may produce transient discomfort characterized by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that

suitable control measures be used in an occupational setting. Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by eye contact, skin contact with the material. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapor, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

Xinya